

**CAMSHAFT: Performer-Plus Hydraulic Roller****CATALOG #: 2208 & 2209****ENGINE: Chevrolet 265-360 c.i.d. V8****RPM RANGE: Idle-5500****CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .500". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 280°	Exhaust 290°
Duration at .050" Lift:	Intake 212°	Exhaust 222°

Lift at cam:	Intake .308"	Exhaust .319"
Lift at valve:	Intake .462"	Exhaust .479"

Timing at .050 Lift:	Open	Close
Intake	1° BTDC	33° ABDC
Exhaust	48° BBDC	6° BTDC

Intake Centerline:	107° ATDC
Lobe Separation:	112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or 7802, Accu-Drive gear drive #7890, or Hex-A-Just Timing Set #7331 with camshaft #2208. #2209 should only be matched with Performer Link set #7801. Do not use late model timing sets designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.Catalog #2208, 2209
Rev. 10/08 - AJ/mc©2008 Edelbrock Corporation
Brochure #63-2208C**CAMSHAFT: Performer-Plus Hydraulic Roller****CATALOG #: 2208 & 2209****ENGINE: Chevrolet 265-360 c.i.d. V8****RPM RANGE: Idle-5500****CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .500". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 280°	Exhaust 290°
Duration at .050" Lift:	Intake 212°	Exhaust 222°

Lift at cam:	Intake .308"	Exhaust .319"
Lift at valve:	Intake .462"	Exhaust .479"

Timing at .050 Lift:	Open	Close
Intake	1° BTDC	33° ABDC
Exhaust	48° BBDC	6° BTDC

Intake Centerline:	107° ATDC
Lobe Separation:	112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or 7802, Accu-Drive gear drive #7890, or Hex-A-Just Timing Set #7331 with camshaft #2208. #2209 should only be matched with Performer Link set #7801. Do not use late model timing sets designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.Catalog #2208, 2209
Rev. 10/08 - AJ/mc©2008 Edelbrock Corporation
Brochure #63-2208C**CAMSHAFT: Performer-Plus Hydraulic Roller****CATALOG #: 2208 & 2209****ENGINE: Chevrolet 265-360 c.i.d. V8****RPM RANGE: Idle-5500****CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .500". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 280°	Exhaust 290°
Duration at .050" Lift:	Intake 212°	Exhaust 222°

Lift at cam:	Intake .308"	Exhaust .319"
Lift at valve:	Intake .462"	Exhaust .479"

Timing at .050 Lift:	Open	Close
Intake	1° BTDC	33° ABDC
Exhaust	48° BBDC	6° BTDC

Intake Centerline:	107° ATDC
Lobe Separation:	112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or 7802, Accu-Drive gear drive #7890, or Hex-A-Just Timing Set #7331 with camshaft #2208. #2209 should only be matched with Performer Link set #7801. Do not use late model timing sets designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.Catalog #2208, 2209
Rev. 10/08 - AJ/mc©2008 Edelbrock Corporation
Brochure #63-2208C**CAMSHAFT: Performer-Plus Hydraulic Roller****CATALOG #: 2208 & 2209****ENGINE: Chevrolet 265-360 c.i.d. V8****RPM RANGE: Idle-5500****CAUTION:** Do not use dual valve springs. Use recommended valve springs with closed pressure of 120-130 lbs., open pressure of 320-340 lbs, and max lift of .500". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 280°	Exhaust 290°
Duration at .050" Lift:	Intake 212°	Exhaust 222°

Lift at cam:	Intake .308"	Exhaust .319"
Lift at valve:	Intake .462"	Exhaust .479"

Timing at .050 Lift:	Open	Close
Intake	1° BTDC	33° ABDC
Exhaust	48° BBDC	6° BTDC

Intake Centerline:	107° ATDC
Lobe Separation:	112°

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or 7802, Accu-Drive gear drive #7890, or Hex-A-Just Timing Set #7331 with camshaft #2208. #2209 should only be matched with Performer Link set #7801. Do not use late model timing sets designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.Catalog #2208, 2209
Rev. 10/08 - AJ/mc©2008 Edelbrock Corporation
Brochure #63-2208C