



CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2204
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°

Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"

Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC

Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
--------------	----------------	----------------

Lobe Separation:	112°
------------------	------

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7801. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2204
Rev. 10/08

©2008 Edelbrock Corporation
Brochure #63-0465



CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2204
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°

Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"

Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC

Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
--------------	----------------	----------------

Lobe Separation:	112°
------------------	------

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7801. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2204
Rev. 10/08

©2008 Edelbrock Corporation
Brochure #63-0465



CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2204
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°

Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"

Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC

Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
--------------	----------------	----------------

Lobe Separation:	112°
------------------	------

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7801. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2204
Rev. 10/08

©2008 Edelbrock Corporation
Brochure #63-0465



CAMSHAFT: Performer RPM Roller Hydraulic
CATALOG #2204
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°

Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"

Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC

Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
--------------	----------------	----------------

Lobe Separation:	112°
------------------	------

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7801. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Catalog #2204
Rev. 10/08

©2008 Edelbrock Corporation
Brochure #63-0465