



**CAMSHAFT: Performer-Plus**

**PART #: 3790**

**ENGINE: Chevrolet & AMC V6 60° 2.8 litre**

**RPM RANGE: Idle to 5500**

**CAUTION:**

Use only stock valve springs.

Use only stock ratio rocker arms.

Duration at .006" Lift:	Intake 253°	Exhaust 263°
Duration at .050" Lift:	Intake 204°	Exhaust 214°

Lift at Cam:	Intake .280°	Exhaust .294°
Lift at Valve:	Intake .420°	Exhaust .442°

Timing at .050" Lift:	<b>Open</b>	<b>Close</b>
Intake:	5° ATDC	29° ABDC
Exhaust:	44° BBDC	10° BTDC



**CAMSHAFT: Performer-Plus**

**PART #: 3790**

**ENGINE: Chevrolet & AMC V6 60° 2.8 litre**

**RPM RANGE: Idle to 5500**

**CAUTION:**

Use only stock valve springs.

Use only stock ratio rocker arms.

Duration at .006" Lift:	Intake 253°	Exhaust 263°
Duration at .050" Lift:	Intake 204°	Exhaust 214°

Lift at Cam:	Intake .280°	Exhaust .294°
Lift at Valve:	Intake .420°	Exhaust .442°

Timing at .050" Lift:	<b>Open</b>	<b>Close</b>
Intake:	5° ATDC	29° ABDC
Exhaust:	44° BBDC	10° BTDC



**CAMSHAFT: Performer-Plus**

**PART #: 3790**

**ENGINE: Chevrolet & AMC V6 60° 2.8 litre**

**RPM RANGE: Idle to 5500**

**CAUTION:**

Use only stock valve springs.

Use only stock ratio rocker arms.

Duration at .006" Lift:	Intake 253°	Exhaust 263°
Duration at .050" Lift:	Intake 204°	Exhaust 214°

Lift at Cam:	Intake .280°	Exhaust .294°
Lift at Valve:	Intake .420°	Exhaust .442°

Timing at .050" Lift:	<b>Open</b>	<b>Close</b>
Intake:	5° ATDC	29° ABDC
Exhaust:	44° BBDC	10° BTDC



**CAMSHAFT: Performer-Plus**

**PART #: 3790**

**ENGINE: Chevrolet & AMC V6 60° 2.8 litre**

**RPM RANGE: Idle to 5500**

**CAUTION:**

Use only stock valve springs.

Use only stock ratio rocker arms.

Duration at .006" Lift:	Intake 253°	Exhaust 263°
Duration at .050" Lift:	Intake 204°	Exhaust 214°

Lift at Cam:	Intake .280°	Exhaust .294°
Lift at Valve:	Intake .420°	Exhaust .442°

Timing at .050" Lift:	<b>Open</b>	<b>Close</b>
Intake:	5° ATDC	29° ABDC
Exhaust:	44° BBDC	10° BTDC