

**CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7168  
ENGINE: Ford 351 c.i.d. Cleveland V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use appropriate valve springs which will accommodate the lift of the camshaft. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 312°	Exhaust 322°
Duration at .050" Lift:	Intake 234°	Exhaust 244°
Lift at cam:	Intake .325"	Exhaust .340"
Lift at valve:	Intake .562"	Exhaust .588"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	59° BBDC	5° ATDC
Centerlines:	Intake: 107°	
Lobe Separation:	112°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7821 or Accu-Drive gear drive #7896. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7168  
Rev. 9/07*

*©2007 Edelbrock Corporation  
Brochure #63-7168C*

**CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7168  
ENGINE: Ford 351 c.i.d. Cleveland V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use appropriate valve springs which will accommodate the lift of the camshaft. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 312°	Exhaust 322°
Duration at .050" Lift:	Intake 234°	Exhaust 244°
Lift at cam:	Intake .325"	Exhaust .340"
Lift at valve:	Intake .562"	Exhaust .588"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	59° BBDC	5° ATDC
Centerlines:	Intake: 107°	
Lobe Separation:	112°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7821 or Accu-Drive gear drive #7896. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7168  
Rev. 9/07*

*©2007 Edelbrock Corporation  
Brochure #63-7168C*

**CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7168  
ENGINE: Ford 351 c.i.d. Cleveland V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use appropriate valve springs which will accommodate the lift of the camshaft. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 312°	Exhaust 322°
Duration at .050" Lift:	Intake 234°	Exhaust 244°
Lift at cam:	Intake .325"	Exhaust .340"
Lift at valve:	Intake .562"	Exhaust .588"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	59° BBDC	5° ATDC
Centerlines:	Intake: 107°	
Lobe Separation:	112°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7821 or Accu-Drive gear drive #7896. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7168  
Rev. 9/07*

*©2007 Edelbrock Corporation  
Brochure #63-7168C*

**CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7168  
ENGINE: Ford 351 c.i.d. Cleveland V8  
RPM RANGE: 1500-6500**



**CAUTION:** Do not use dual valve springs. Use appropriate valve springs which will accommodate the lift of the camshaft. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 312°	Exhaust 322°
Duration at .050" Lift:	Intake 234°	Exhaust 244°
Lift at cam:	Intake .325"	Exhaust .340"
Lift at valve:	Intake .562"	Exhaust .588"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	59° BBDC	5° ATDC
Centerlines:	Intake: 107°	
Lobe Separation:	112°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7821 or Accu-Drive gear drive #7896. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7168  
Rev. 9/07*

*©2007 Edelbrock Corporation  
Brochure #63-7168C*