



EDELBROCK / RUSSELL CHROME STEEL FUEL LINES
For Performer and Thunder Series Carburetors
Catalog #s, 8128, 8132 and 8133
INSTALLATION INSTRUCTIONS

PLEASE study these instructions carefully before beginning this installation. Most installations can be accomplished with common tools and procedures. However, you should be familiar with and comfortable working on your vehicle. If you do not feel comfortable performing this installation, it is recommended to have the installation completed by a qualified mechanic. If you have any questions, please call our **Technical Hotline at: 1-800-416-8628**, 7:00 am - 5:00 pm, Pacific Standard Time, Monday through Friday.

IMPORTANT NOTE: Proper installation is the responsibility of the installer. Improper installation will void your warranty and may result in poor performance and engine or vehicle damage.

WARNING! Make sure to perform the installation in a well ventilated area away from any potential fire hazards. Gasoline fumes are toxic and are highly flammable. Prior to starting the installation, make sure to eliminate all potential fire hazards as fuel leakage can occur when loosening the fuel system connections. Make sure to check and repair any fuel leaks prior to operating the vehicle.

PLEASE complete and mail your warranty card. Be sure to write the model number of this product in the "Part # ____" space. **THANK YOU.**

DESCRIPTION: These attractive chrome steel fuel lines provide a clean and simple method of finishing off your fuel system. These fuel lines fit Performer-Series and Thunder-Series AVS carburetors. They feature either a 3/8" hose barb or a 40 micron, billet aluminum fuel filter with a -6AN inlet. Specific applications are listed below:

KIT DESCRIPTION:

- 8128** - With *Polished Fuel Filter* (Replacement filter - #8129)
- 8132** - With 3/8" Hose Barb End Inlet - No Fuel Filter
- 8133** - With *Blue Anodized Fuel Filter* (Replacement filter - #8130)

KIT CONTENTS:

- 1 Fuel Line
- 1 Fuel Filter (8128, 81330 ONLY)
- 1 3/8" Hose Barb Fitting (8132 ONLY)
- 2 Banjo Bolt
- 4 Washer

INSTALLATION PROCEDURE

1. Remove fuel inlet fitting from carburetor.
2. Attach new fuel line to carburetor using washers and banjo bolt as shown (**See Figure 1**). Do not fully tighten.
3. Install fuel filter or barb fitting (#8132 Only) using a light coat of oil on the threads.
4. Adjust the fuel line for straightness if necessary (**See Figure 2 for reference**).
5. Tighten all connections and attach appropriate fuel line from fuel pump or fuel pressure regulator.
6. Start engine or turn on electric fuel pump (if independently switched). Check for leaks.

CAUTION: If leaks exist, immediately shut off engine (or electric fuel pump) and fix leaks before continuing!

