

ALUMINUM FUEL RAIL KIT For B/B Chevy Victor Tunnel Ram EFI Manifold, #70855 Catalog #3659 INSTALLATION INSTRUCTIONS

PLEASE study these instructions carefully before beginning this installation. Most installations can be accomplished with common tools and procedures. However, it is recommended to have a strong familiarity with working on automotive fuel systems before attempting this installation. If you do not feel comfortable performing this installation or have never worked with automotive fuel systems before, it is highly recommended to have the installation completed by a qualified mechanic with strong familiarity with automotive service procedures. If you have any questions, please call our **Technical Hotline at: 1-800-416-8628**, 7:00 am - 5:00 pm, Pacific Standard Time, Monday through Friday.

WARNING! Always work in a well-ventilated area when working with gasoline as the vapors are toxic and are highly flammable. Be aware of any sources of heat or sparks, such as drop lights or space heaters. Do not smoke and do not allow those around you to smoke during this installation.

Proper installation is the responsibility of the installer. Improper installation will void all manufacture's standard warranties and may result in poor performance and engine or vehicle damage.

• **DESCRIPTION:** Aluminum Fuel Rail Kit #3659 is designed to be used with the Edelbrock Big Block Chevy Victor Tunnel Ram EFI Intake Manifold #70855. It's compatible with standard height injectors (2.50" o-ring center to center spacing) such as Edelbrock #3687-Single and #3686-Set of eight. Please visit the Edelbrock website at www.edelbrock.com for more details. This fuel rail kit may also be used in custom applications where manifold #70855 is not being used. For custom applications, fuel rail stands are available separately for use with Pico-style injectors (PN 3619).

Kit includes the following:

- □ 2 Machined Fuel Rail (Ends are tapped for -8 AN [3/4-16 SAE] fittings)
- □ 4 Fuel Rail Spacer (Ø.562 O.D. by .50" thick)
- □ 4 1/4-20 x 1-3/4" Hex Flange Bolt
- ☐ 4 1/4" Flat Washer
- **FUEL RAIL KIT:** Apply a small amount of silicone or other adhesive to attach the spacers to the fuel rail bosses on the manifold. Apply 0-ring lube to the 0-rings on the injectors and fittings (fittings and injectors not included). Install the fittings and injectors onto the fuel rails and secure the fuel rails to the manifold using the supplied hardware.
- FINAL CHECKS: Once assembly is complete, check the following:
 - ☐ Check to make sure each injector is properly seated into their respective bores on the fuel rails and manifold. The injectors should be able to rotate freely. This will prevent any air and/or fuel leaks.
 - Turn the fuel system power "ON" but DO NOT start the engine. Check all fittings and injectors for any leaks. If leaks are present, turn the power "OFF" immediately and repair any leaks before starting the engine.



Edelbrock LLC • 2700 California St. • Torrance, CA 90503 Tech-Line: 800-416-8628

 Catalog #3659
 ©2013 Edelbrock LLC

 Rev. 12/13/13 QT
 Brochure #63-3659